

Command-type TFT-LCD Module

Middle Model 3.5 inch

RoHS

■ Features


This TFT-LCD module/control board displays content, including stored JPEG images and text with internal fonts, by way of a simple command set. Language font, interface, SD card functions are added to the Low series.

■ Specifications

Item \ Series		LC035MA1RE
LCD panel	Display size class[inch]	3.5
	Pixels [dot]	320×240(QVGA)
	Active area [W×H mm]	70.08×52.56
	Luminance [cd/m ²]	400
	Viewing angles [deg]	Bottom = 70, Top = 50, Left = 70, Right = 70
	Backlight type	LED
	LED lifetime [h] ※1	Min. 20,000
Interface		USB2.0 Full Speed & RS232C(115.2kbps Max) & RS485
Touch panel	Type	Resistive
	Active area [W×H mm]	70.08×52.56
	Surface durability [touches]	1,000,000
	Surface hardness	3H
Character		Japanese(kanji, katakana, hiragana, Alphameric characters), Korean, Chinese(Simplicity / Tradition), European
Font code		Japanese, Alphameric characters : FA UD Gothic R, Korean : FZHeiTi, Chinese : FZLanTingHei, European : NimbusSanL Regular
Font size [pixel]		Scalable (Variable) W:12×128, H:12×128
Image storage media		SD card (SDHC Up to 4GB)
Max memory for screen images		Background 4,000, Icon 16,000 (SD card 4GB)
Supply voltage [V]		5.0
Power consumption [W]		2.0
Operating temperature [°C]		-10~+60
Storage temperature [°C]		-30~+70
Operating temperature [%RH] no condensation		10~90
Storage temperature [%RH] no condensation		10~90
Outer dimensions [W×H×T mm]		96.0×72.0×17.3
Weight [g]		approx. 140

※1: LED lifetime = hours for the module luminance to decrease to 50% of original measured brightness at Ta = 25°C.

■ Appearance, outer dimensions



LC035MA1RE

<Contact>

Futaba Corporation Tokyo Sales Office Akihabara Bldg. 5F, 19 Kandamatsunaga-cho Chiyoda-ku, Tokyo, 101-0023, Japan
 TEL : 81-3-4316-4821 FAX : 81-3-4316-4823

URL <http://www.futaba.co.jp/>